

# Sandiacre Novus



## **Features**

- High Speed Continuous Motion
- Up to 220 bags per minute
- Servo-driven motors
- Allen-Bradley ControlLogix with Kinetix 6000 system allows for wide speed range and wide range of bag styles
- Quad Pack Capability
- Three model sizes: 250, 350 & 380

- Environmental protection with fully enclosed stainless steel construction and stainless steel top tray
- Slim-line footprint
- Reduced setup times
- Modular assemblies for quick changeover

BW Packaging Systems represents the collective capabilities of Barry-Wehmiller packaging companies including, Accraply, BW Flexible Systems, BW Integrated Systems, Pneumatic Scale Angelus and Synerlink. Through their diverse capabilities, these companies can collectively provide everything from a single piece of equipment to fully integrated packaging systems for a wide range of industries, including: food and beverage, personal care, container manufacturing, pharmaceutical and medical devices, household products, paper products and textiles, industrial and automotive, and converting, printing and publishing. For more information, go to BWPackagingSystems.com



VFFS

## Sandiacre Novus

### **Speed Through Continuous Motion**

The NOVUS is a high-speed leader with the latest in continuous motion technology. Available in a 250, 350 and 380 model, all feature low maintenance with modular assemblies for quick changeover and improved accessibility.

The NOVUS servo-driven system features off-the-shelf Allen-Bradley ControlLogix control system with Kinetix 6000 system. Take full advantage of the wide speed range and wide range of bag styles with full configuration available for polyethylene or heatseal applications. The slim-line footprint saves valuable floor space while the fully enclosed stainless steel construction offers environmental protection.

### **Production Rate**

Up to 200 bags per minute

#### Package Range

Min Width:	60mm (2.36″)
Min Length:	60mm (2.36″)
Max Width:	380mm (14.96″)
Maximum Length:	Infinitely variable from 60mm

#### **Power Requirements**


20 Amp, 3-phase neutral and earth, 10KVA

#### **Air Requirements**

Heat-seal mode (with air operated vacuum pump) = 600 l/min Poly-sealing mode = additional 1,800 l/min (Air consumption is normalised).

A few of the many available options include various jaw options, transverse zip applicator, full bag conveyors, Ethernet connection for MIS/Scada systems, block bottom/gusset bag, tear notches, code daters, gas flushing, static eliminators and tucking devices. We have extensive experience in integrating a wide variety of feed systems including scales, augers, volumetrics and pumps for a wide variety of applications.

Let us customize a NOVUS to meet your specific requirements, whether it is a specific bag style or a production need the NOVUS is a proven high speed performer.



Reduce setup times with film splicing, film reel runout device and easy thread film path



Continuous Motion Reciprocating Jaws for the Strongest Seals

#### America

225 Spartangreen Blvd. Duncan SC 29334 USA t. +1 (864) 486 4000

#### **United Kingdom**

101 Lilac Grove, Beeston Nottingham NG9 1PF UK t. +44 (0) 115 967 8787

#### Italy

Via Trieste, 53 35035 Mestrino (PD) Italy t. +39 049 900 6 511

BW Flexible Systems is a global manufacturer of packaging systems that fill and bag thousands of food and non-food products. Our packaging systems are designed and manufactured to maximize the efficiency and lifetime value of our customers' packaging lines. Our range of machinery includes form-fill-seal, feeding, bag filling and sealing, pouch-making equipment, flow-wrap, reclosable packaging solutions, palletizing, stretch-wrapping and more. For more information, go to *bwflexiblesystems.com* 

